



1133 South Carpenter Avenue Suite A, Kingsford, MI 49802 - P: +1 844-442-6977 - - www.mmindustrialsales.com

# MM-IBA 6300

## Low-Pressure Industrial Breathing Air Compressor Fluid

MM-IBA 6300 is formulated to provide complete compatibility with a wide variety of OEM and aftermarket rotary screw compressor lubricants. Flushing is not required to switch to MM-IBA 6300; in most cases, it can be added directly on top of the existing compressor oil. Its advanced formulation helps avoid costly lubricant-contamination mistakes and helps streamline product inventory. MM-IBA 6300 is also formulated to provide outstanding resistance against wear, rust, corrosion and sludge buildup, and to provide 10,000 hours of service.

### ATTRIBUTES

- 10,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

### TYPICAL LUBRICANT PROPERTIES

MM-IBA 6300 Grades	32	46	68
Viscosity cSt @ 40°C	32	46.1	67
Viscosity cSt @ 100°C	5.4	6.7	8.7
Flash Point °F (°C)	435 (224)	450 (232)	478 (248)
Copper Corrosion	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0